



Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Date: _____
Approval: _____
Construction: _____
Unit #: _____
Drawing #: _____




KEY FEATURES:

- LED display
- Smart Kit included
- Quiet operation
- Multiple fan speeds (LOW/MED/HI/TURBO)
- Easy to remove filter
- Auto-swing for vertical and horizontal louvers
- Can be installed up to 2" from the ceiling



SPECIFICATIONS:

Indoor Model			CH-PRO24MASTWM-230VI
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	
Heating	Rated Capacity	Btu/h	
Minimum Circuit Ampacity (MCA)		A	3
Max. Fuse		A	15
Indoor Air Flow (Hi/Mi/Lo)		CFM	
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	5/8"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	3/8"/5/8"
Dehumidification		Pnt/H	
Communication wiring			14AWG*4
Indoor	Dimension (W×D×H)	Inch	47.13 x 11.02 x 14.61
	Packing (W×D×H)	Inch	50.39x14.17x17.91
	Net/Gross Weight	lbs	43.65/55.56



Capacity	Body Code	Unit	W	D	H
6k~12k	B	mm	857	231	300
		inch	33-3/4	9-1/8	11-3/4
18k	C	mm	1024	246	321
		inch	40-1/4	9-3/4	12-5/8
24k~36k	D	mm	1197	280	371
		inch	47-1/8	11	14-5/8