

Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Date: _____
Approval: _____
Construction: _____
Unit #: _____
Drawing #: _____



KEY FEATURES:

- Double blower wheel
- Refrigerant Sensor
- Auto-Swing for horizontal louvers
- 46° Freeze Protection
- Smart Kit Ready
- Turbo Mode
- Follow Me Mode
- Smart kit Include



SPECIFICATIONS:

Indoor Model			CH-RSH09MMC
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	9,000 (3,700~13,700)
Heating	Rated Capacity	Btu/h	9,000 (4,400~16,100)
Minimum Circuit Ampacity (MCA)		A	3
Max. Fuse		A	15
Indoor Air Flow (Hi/Mi/Lo)		CFM	441.18/376.47/323.53/264.71
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	40/37/26
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	5/8"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4" - 1/2"
Dehumidification		Pnt/H	1.20
Communication wiring			14AWG*4
Indoor	Dimension (W×D×H)	inch	31.26x7.87x24.45
	Packing (W×D×H)	inch	34.06x11.02x28.31
	Net/Gross Weight	lbs.	32.85/41.45

