

Job Name:
Location:
Engineer:
Submitted to:
Submitted by:
Reference:

Date:
Approval:
Construction:
Unit #:
Drawing #:



KEY FEATURES:

- Double blower wheel
- Refrigerant Sensor
- Auto-Swing for horizontal louvers
- 46° Freeze Protection
- Smart Kit Ready
- Turbo Mode
- Follow Me Mode
- Smart kit Include



SPECIFICATIONS:

Indoor Model			CH-RSH12MMC
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	12,000
Heating	Rated Capacity	Btu/h	12,000
Minimum Circuit Ampacity (MCA)	A		3
Max. Fuse	A		15
Indoor Air Flow (Hi/Mi/Lo)	CFM		441.18/376.47/323.53/264.71
Indoor Noise Level (Hi/Mi/Lo)	dB(A)		40/37/26
External static presure (SlimDuct/AHU only)	in. WG		
Drainage water pipe diameter	inch		5/8"
Diameter of refrigerant pipe (Liquid/Gas Side)	Inch		1/4" - 1/2"
Dehumidification	Pnt/H		1.20
Communication wiring			14AWG*4
Indoor	Dimension (WxDxH)	inch	31.26x7.87x24.45
	Packing (WxDxH)	inch	34.06x11.02x28.31
	Net/Gross Weight	lbs.	32.85/41.45

