

Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Date: _____
Approval: _____
Construction: _____
Unit #: _____
Drawing #: _____



KEY FEATURES:

- Compatible with Regular or Hyper Heat Pump
- Refrigerant Sensor Built-in
- Multiple speed mode
- SmartKit Technology Ready
- Wall Thermostat Included
- Remote Control Included
- Gold Fin



SPECIFICATIONS:

Indoor Model			CH-RS06-12MDT-MS
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	
Heating	Rated Capacity	Btu/h	
Minimum Circuit Ampacity (MCA)		A	3
Max. Fuse		A	15
Indoor Air Flow (Hi/Mi/Lo)		CFM	
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	1"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4"/3/8"
Dehumidification		Pnt/H	
Communication wiring			14AWG*4
Indoor	Dimension (WxDxH)	Inch	27.56 x 19.92 x 7.87
	Packing (WxDxH)	Inch	33.86 x 21.26 x 11.22
	Net/Gross Weight	lbs.	39.46/46.74

Installation place

The distance between the mounted indoor unit should meet the specifications illustrated in the following diagram.

