

Job Name: _____
Location: _____
Engineer: _____
Submitted to: _____
Submitted by: _____
Reference: _____

Date: _____
Approval: _____
Construction: _____
Unit #: _____
Drawing #: _____



KEY FEATURES:

- Single or Multi-Zone Application
- Humidity Sensor
- Easy access E-Box and PCB
- Easy-to-remove blower wheel
- Auto-Swing for vertical and horizontal louvers
- Smart Kit Included
- Can be installed up to 2" from ceiling
- Compatible with Regular and Hyper Heat Outdoor units




SPECIFICATIONS:

Indoor Model			CH-RH06MASTWM-230VI
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	6,000
Heating	Rated Capacity	Btu/h	7,000
Minimum Circuit Ampacity (MCA)		A	3
Max. Fuse		A	15
Indoor Air Flow (Hi/Mi/Lo)		CFM	382.6 / 323.7 / 229.6 / 176.6
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	36.5/32.5/22
External static pressure (SlimDuct/AHU only)		in. WG	
Drainage water pipe diameter		inch	5/8"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4"/3/8"
Dehumidification		Pnt/H	0.63
Communication wiring			AWG 14-4
Indoor	Dimension (WxDxH)	Inch	33.74 x 9.09 x 11.81
	Packing (WxDxH)	Inch	36.22x12.20x14.57
	Net/Gross Weight	lbs.	22.93/29.32

ASTORIA

Units: in



Dimension (WxDxH)
33.74 x 9.09 x 11.81