

Job Name: _____

Location: _____

Engineer: _____

Submitted to: _____

Submitted by: _____

Reference: _____

Date: _____

Approval: _____

Construction: _____


Unit #: _____

Drawing #: _____


KEY FEATURES:

- Heat Pump operation (heating and cooling)
- Inverter-driven DC compressor for variable capacity
- 24V communicating controls compatible with a communicating indoor unit
- Available from 1.5 to 5 tons (18,000–60,000 BTU)
- R-454B refrigerant
- Variable-speed outdoor fan motor
- Soft start with very low starting current
- High part-load efficiency (excellent SEER2)
- Wide operating range for both cooling and heating
- Built-in diagnostics and fault reporting
- Quiet operation due to inverter modulation

NOTES:



Indoor Model			CH-MP30AHU24V
Power supply		V, Ph, Hz	115/208/230V,60Hz
Communication wiring			AWG 20x2
Cooling	Capacity	Btu/h	30,000 (7,300~30,400)
	Input	w	3,261
	Rated current	A	13.9
	EER/EER2	Btu/w	9.1
	SEER/SEER2	Btu/w	17.6
Heating at 47 °F	Capacity	Btu/h	30000 (7,100~32,400)
	Input	W	2765 (420 ~2,920)
	Rated current	A	12.3 (2.3 ~13.0)
	COP	W/W	3.18
	HSPF4/HSPF2-4		9.2
	HSPF5/HSPF2-5		7.2
Indoor fan motor		Qty	1
		Input	250
		RLA	5.5/4.0
Indoor air flow (Turbo/Hi/Med/Lo) (No duct)		CFM	989 / 896 / 803 / 710 / N/A
ESP (range)		In.wg.	0-0.8 In.W.G
Indoor noise level (Hi/Med/Lo)		dB(A)	53/47/44/39/N/A
Dehumidification		L/H	6.61
Indoor unit	Dimensions (WxDxH)	inch	21.02 x 17.52 x 45.00
	Packing (WxDxH)	inch	26.57 x 20.87 x 48.62
	Net/Gross weight	lbs	109/130
Drainage water pipe diameter		inch	3/4"
Refrigerant piping (Liquid side/Gas side)		inch	3/8" 3/4"
Design pressure		PSIG	550 / 340
Controller			120N/24V
Room temperature	Cooling	F	60~90
	Heating	F	60~90



Dimensions		18/24/30k		36/48/60k	
		inch	mm	inch	mm
A	Model Height	45	1143	49	1245
B	Model Width	17-1/2	445	21	534
C	Supply Air Opening Width	15-5/8	397	19-1/8	486
D	Return Air Opening Width	15-1/8	384	18-5/8	473
E	Model Depth	21	534	21	534
F	Supply Air Opening Depth	10-1/4	260	10-1/4	260
G	Return Air Opening Depth	18-3/4	476	18-3/4	476
H	Supply Air Opening Clearance	15/16	24	15/16	24
I	Return Air Opening Side Clearance	1-1/4	32	1-1/4	32
J	Return Air Opening Front Clearance	1-1/2	38	1-5/8	41
K	Return Air Opening Back Clearance	5/8	16	5/8	16