

Job Name: _____

Location: _____

Engineer: _____

Submitted to: _____

Submitted by: _____

Reference: _____

Date: _____

Approval: _____

Construction: _____


Unit #: _____

Drawing #: _____

KEY FEATURES:


- Cooling-only outdoor unit
- Inverter-driven DC compressor
- 24V communicating controls
- Available in 1.5–3 ton capacities
- R-454B refrigerant
- Variable-speed condenser fan
- Soft start / low inrush current
- Quiet operation
- High SEER2 efficiency
- Excellent humidity removal through inverter capacity control

NOTES:




Outdoor Model			CH-OMN24CL24V-230VO
Power supply		V, Ph, Hz	115/208/230V,60Hz
Min. circuit ampacity		A	19
Max. fuse		A	20
Compressor	Model		KTM240D46UKT2
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	N/A
	Input	w	805/2045
	Rated current (RLA)	A	0.8
	Refrigerant oil	oz	VGA74
Outdoor fan motor	Qty		1
	Input	w	N/A
	RLA	A	0.8
	Speed	r/min	N/A
Outdoor air flow (Max)		CFM	1,766
Outdoor noise level (Max)		dB(A)	56
Throttle type			EXV
Outdoor unit	Dimensions (WxDxH)	inch	35.04 x 13.46 x 26.50
	Packing (WxDxH)	inch	39.17 x 15.67 x 29.13
	Net/Gross weight	inch	89.29/97.00
Refrigerant	Type		R454B
	Precharge	ft	24.6
Additional charge for 1/4 inch liquid pipe		oz	
Additional charge for 3/8 inch liquid pipe		oz	.7 oz/ft
Refrigerant piping	Liquid side/Gas side	inch	3/8" 3/4"
	Max. pipe length	ft	164'
	Max. difference in level	ft	82'
Ambient temperature	Cooling	F	-13~122
	Heating	F	/

Outdoor Unit Dimension



Installation Instruction For Outdoor Unit



☒ Meets all spatial requirements shown in Installation Clearance Requirements above.