


Job Name:	_____	Date:	_____
Location:	_____	Approval:	_____
Engineer:	_____	Construction:	_____
Submitted to:	_____	Unit #:	_____
Submitted by:	_____	Drawing #:	_____
Reference:	_____		_____

KEY FEATURES:

- Inverter-Driven Cooling System
- High SEER2 Efficiency
- R-454B Refrigerant
- Quiet Operation
- Soft Start Technology
- Variable-Speed Performance
- Multi-Position Air Handler
- Wired Controller Included
- Refrigerant Leak Detection
- Aluminum Coil with Gold Fin
- Auto Restart Function
- Turbo & Sleep Modes


NOTES:



Indoor Model			CH-STM24AHU24V
Power supply		V, Ph, Hz	115/208/230V 1ph, 60Hz
Communication wiring		AWG	20-2
Cooling	Capacity	Btu/h	22000 (10100~27600)
	Input	w	1880 (830~2850)
	Rated current	A	3.7~13.5
	EER/EER2	Btu/w	11.7
	SEER/SEER2	Btu/w	17.5
Heating at 47 °F	Capacity	Btu/h	25000 (7000~32200)
	Input	W	1980 (455~2590)
	Rated current	A	2.5~11.4
	COP	W/W	3.8
	HSPF4/HSPF2-4		10.5
	HSPF5/HSPF2-5		/
Indoor fan motor	Qty		1
	Input		/
	RLA		3
Indoor air flow (Turbo/Hi/Med/Lo) (No duct)		CFM	824.0 / 759.3 / 694.5 / 629.8
ESP (range)		ln.wg.	0-0.8
Indoor noise level (Hi/Med/Lo)		dB(A)	53/51/48/37.5
Dehumidification		L/H	5.28
Indoor unit	Dimensions (WxDxH)	inch	20.28 x 15.71 x 36.54
	Packing (WxDxH)	inch	22.83 x 19.49 x 42.91
	Net/Gross weight	lbs	111.33/91.49
Drainage water pipe diameter		inch	3/4"
Refrigerant piping (Liquid side/Gas side)		inch	3/8"/3/4"
Design pressure		PSIG	550/340
Controller			120N(X6), 120N (X6W), Wireless, 24V T-Stat
Room temperature	Cooling	F	60~90
	Heating	F	61~86

Outdoor Model			CH-PQ24-230VO
Power supply		V, Ph, Hz	115/208/230V 1ph, 60Hz
Min. circuit ampacity		A	19
Max. fuse		A	20
Compressor	Model		KTM240D46UKT2
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	25,930
	Input	w	2,045
	Rated current (RLA)	A	14
	Refrigerant oil	oz	VG74 21
Outdoor fan motor	Qty		1
	Input	w	80
	RLA	A	1
	Speed	r/min	810/700/450
Outdoor air flow (Max)		CFM	1,765.8
Outdoor noise level (Max)		dB(A)	59
Throttle type			EXV
Outdoor unit	Dimensions (WxDxH)	inch	35.04 x 13.46 x 26.50
	Packing (WxDxH)	inch	39.17 x 15.67 x 29.13
	Net/Gross weight	inch	102.29/109.13
Refrigerant	Type		R454B
	Precharge	ft	25
Additional charge for 1/4 inch liquid pipe		oz	
Additional charge for 3/8 inch liquid pipe		oz	0.7
Refrigerant piping	Liquid side/Gas side	inch	3/8"/3/4"
	Max. pipe length	ft	164
	Max. difference in level	ft	82
Ambient temperature	Cooling	F	-22 ~ 122
	Heating	F	-22~75

Indoor Unit Dimension



Dimensions		Model(Btu/h)	18K/24K		30K/36K	
			inch	mm	inch	mm
A	Model Height		36.5	928	49	1017
B	Model Width		20.3	515	21	559
C	Supply Air Opening Width		17.4	442	18.8	478.6
D	Return Air Opening Width		19.4	493.8	21.2	537.8
E	Model Depth		15.7	399	21	4.83
F	Supply Air Opening Depth		10.4	265.2	9.3	235.4
G	Return Air Opening Depth		10.3	261	13.1	332.5
H	Supply Air Opening Clearance		1.1	29.1	1.6	41
I	Return Air Opening Side Clearance		0.42	10.6	0.42	10.6
J	Return Air Opening Front Clearance		0.47	12	0.63	16

PEAQ

