



INSTALLATION KITS



WATCH OUR
INFORMATIONAL
VIDEO



Proud Sponsors





Our bundled installation kit offers ease and convenience for HVAC technicians while providing a long-lasting, quality product that customers will not have to replace.

- 99.9% Copper (ASTM B-280 C12200)
- Pre-insulated (ASTM D154)
- UV & UV-C Resistant
- Pre-flared
- UL94 Certificate

Includes 4/16 AWG Connecting Cable, Rubber Drain Hose, Bandage Tape, Wall Sleeve, and Neoprene

Line Set Model 3/8"	Line Set Model 1/2"	Line Set Diameter (Liquid/Gas Side)*	Cooper Pipe thickness(inch)	Pipe Insulation Thickness & Rating	Copper Line Length	4/16 AWG Cable	Rubber Drain Hose
PJX-N1-C16FTW-MAX	PJX-N1-C16FTW-MAX-i05	1/4" – 3/8"	1/4"*0.032" + 3/8"*0.032"	3/8", R-2.5	16 FT	18 FT	16 FT
PJX-N1-C25FTW-MAX	PJX-N1-C25FTW-MAX-i05	1/4" – 3/8"	1/4"*0.032" + 3/8"*0.032"	3/8", R-2.5	25 FT	29.5 FT	16 FT
PJX-N1-C50FTW-MAX	PJX-N1-C50FTW-MAX-i05	1/4" – 3/8"	1/4"*0.032" + 3/8"*0.032"	3/8", R-2.5	50 FT	55.8 FT	16 FT
PJX-N2-C16FTW-MAX	PJX-N2-C16FTW-MAX-i05	1/4" – 1/2"	1/4"*0.032" + 1/2"*0.032"	3/8", R-2.5	16 FT	18 FT	16 FT
PJX-N2-C25FTW-MAX	PJX-N2-C25FTW-MAX-i05	1/4" – 1/2"	1/4"*0.032" + 1/2"*0.032"	3/8", R-2.5	25 FT	29.5 FT	16 FT
PJX-N2-C50FTW-MAX	PJX-N2-C50FTW-MAX-i05	1/4" – 1/2"	1/4"*0.032" + 1/2"*0.032"	3/8", R-2.5	50 FT	55.8 FT	16 FT
PJX-N3-C16FTW-MAX	PJX-N3-C16FTW-MAX-i05	3/8" – 5/8"	3/8"*0.032" + 5/8"*0.036"	3/8", R-2.4	16 FT	18 FT	16 FT
PJX-N3-C25FTW-MAX	PJX-N3-C25FTW-MAX-i05	3/8" – 5/8"	3/8"*0.032" + 5/8"*0.036"	3/8", R-2.4	25 FT	29.5 FT	16 FT
PJX-N3-C50FTW-MAX	PJX-N3-C50FTW-MAX-i05	3/8" – 5/8"	3/8"*0.032" + 5/8"*0.036"	3/8", R-2.4	50 FT	55.8 FT	16 FT
PJX-N4-C25FTW-MAX		3/8" – 3/4"	3/8"*0.032" + 3/4"*0.040"	3/8", R-2.3	25 FT	29.5 FT	16 FT
PJX-N4-C50FTW-MAX		3/8" – 3/4"	3/8"*0.032" + 3/4"*0.040"	3/8", R-2.3	50 FT	55.8 FT	16 FT
PJX-N6-C25FTW-MAX		3/8" – 7/8"		3/8", R-2.2	25 FT	29.5 FT	16 FT
PJX-N6-C50FTW-MAX		3/8" – 7/8"		3/8", R-2.2	50 FT	55.8 FT	16 FT

*Note: Some of our light commercial units have adapters for the line sets.

INSULATION MATERIAL: WHITE PE INSULATION STYLE

- Flame Resistant M1/B1
- UV Resistant
- UL94 Certificate

Proud Sponsors

