

Job Name:	_____	Date:	_____
Location:	_____	Approval:	_____
Engineer:	_____	Construction:	_____
Submitted to:	_____	Unit #:	_____
Submitted by:	_____	Drawing #:	_____
Reference:	_____		



KEY FEATURES:

- Auto restart function / Adjustable static pressure
- WIFI ready / Quiet operation
- Multi position / Intelligent air flow
- Multiple fan speeds
- Anti-cold air function
- Refrigerant leak detect
- Auxiliary heater
- Fast cool/heat function
- Sleep mode / Turbo mode
- Aluminium coil
- Gold fin



SPECIFICATIONS:

Indoor Model			CH-RS18MAHU
Power Supply	Rated	V, Ph, Hz	208-230V, 1Ph, 60Hz
Cooling	Rated Capacity	Btu/h	18,000
Heating	Rated Capacity	Btu/h	18,000
Minimum Circuit Ampacity (MCA)		A	3.5
Max. Fuse		A	15
Indoor Air Flow (Hi/Mi/Lo)		CFM	618.0 / 576.8 / 529.7 / 488.5
Indoor Noise Level (Hi/Mi/Lo)		dB(A)	42/39.5/33
External static pressure (SlimDuct/AHU only)		in. WG	0.8
Drainage water pipe diameter		inch	3/4"
Diameter of refrigerant pipe (Liquid/Gas Side)		Inch	1/4"/1/2"
Dehumidification		Pnt/H	3.59
Communication wiring			AWG 14-4
Indoor	Dimension (W×D×H)	Inch	17.52 x21.02 x 45
	Packing (W×D×H)	Inch	20.87 x 26.57 x 48.62
	Net/Gross Weight	lbs.	104.72/125.66

